



**KNUDSON**

# KFS-35C CASSETTES

FRAMEMAKER ACCESSORY – INTERCHANGEABLE ON POWER PACK

FRAMEMAKER  
ACCESSORY



CASSETTE  
OPTIONS FOR  
KFS-35C

FEATURES	KFS-35C CASSETTE
Steel Gauge Range	25-16 Gauge (Metric)
Number of Forming Stations	8
Maxium Speed	60 Feet / Minute
Drive Power	Hydraulic Motor
Width	35" / 0.89 m
Height	32" / 0.81 m
Weight	Approximately 1,125 pounds / 510 kilograms
Configuration	Component Cassette-Based
Flange Height Sizes	Based on Chosen Profile + Coil Size

KMI #	DESCRIPTION	COMPONENT	COIL	THICKNESS
#333	(Hat) Furring Channel	050F150	3.55" ( +/- )	20-16 Gauge
#334	(Hat) Furring Channel	150F125	5.88" (max)	25-16 Gauge
#335A	U-Channel	150U050	2.31"	25-16 Gauge
#335B	U-Channel	213U100	4.06"	
#335C	U-Channel	313U150	6.06"	
#337	(Hat) Furring Channel	150F300	7.20" ( +/- )	20-16 Gauge
#338	Corner Bead	CT112	2.63" (max)	24-18 Gauge
#342	(Hat) Furring Channel	087F125	4.65" (max)	25-16 Gauge
#343	(Hat) Furring Channel	045F050M	185 mm	25-16 Gauge
#344	(Hat) Furring Channel	025F050M	145 mm	0.5 mm - 0.7 mm
#345	(Hat) Furring Channel	036F040M	158 mm	0.5 mm - 0.7 mm
#346	(Hat) Furring Channel	017F015M	75 mm	0.5 mm - 1.1 mm
#348A	(Hat) Furring Channel	150F125	5.82" ( +/- )	25-16 Gauge
#348B	(Hat) Furring Channel	150F125	5.39" ( +/- )	
#349	Resilient Channel	Resilient Channel	3.20"	22-16 Gauge
#350	(Hat) Furring Channel	022F032M	10 mm	0.5 mm - 1.0 mm
#374	(Hat) Furring Channel	150F150	6.22"	22-16 Gauge



**KNUDSON MFG, INC.**

10401 West 120<sup>th</sup> Avenue  
Broomfield, CO 80021 USA

**KNUDSONMFG.COM**

+1 (303) 469-2101